

## APS152EMG SERIES:



### 120-150 Watts / Single Output

- 7.09 x 2.83 x 1.71" UL94V-0 Plastic Case (Desktop)

### Features:

- Universal AC Input (90~264 VAC Input Range)
- EISA, CEC Level IV Compliant (12~24V Models only)
- High Efficiency Operation (87-90%)
- 2 or 3 Prong AC Inlet Options (Safety Class I or II)
- Class B Emissions
- International Safety Approvals (Medical & ITE)
- 2 Year Warranty

### INPUT:

Input Voltage	90~264 VAC (Universal AC Input)
Input Frequency	47-63Hz
Inrush Current	16Arms at 230Vac 50Hz Cold Start
Input Current	1.4A @ 115 VAC / 0.7A @ 230 VAC Maximum
Input Protection	Dual Fuse
Hold-Up Time	15 / 30 ms @ 115 / 230 VAC Minimum
Leakage Current	<300 $\mu$ A @ 240 VAC Maximum
Harmonics	EN61000-3-2 Class D Compliant
Green Power	Less than 0.5W @ 230 VAC (No Load)

### GENERAL:

Efficiency	91% typical
Operating Temperature	0-40°C, derate linearly to 50% Load at 50°C
Storage Temperature	-20°C to +85°C
Over-Temp Protection	>85°C Shutdown (Ambient)
Cooling	Convection Cooled
OverTemp Protection	Installed
Operating Humidity	5-95% RH, Non-Condensing
Vibration	5 ~ 50 Hz, acceleration 7.35 m/s*s on X,Y and Z Axis
MTBF	>50k Hrs (according to MIL-HBK-217F) at 25°C

### OUTPUT:

Minimum Load	None
Line Regulation	$\pm$ 0.1% max
Load Regulation	$\pm$ 2.0% max
Ripple & Noise	$\pm$ 1% typ. pk-pk @ 20MHz
Overload Protection	110-135% of max power (Foldback)
Over Voltage	Latching before 130% of nominal
Short Circuit Protection	Continuous (auto-recovery)
Transient Response	recovers <1ms following a 25% load change
Switching Topology	Fixed Flyback Circuit
Switching Frequency	40~65KHz

### APPROVALS:

Emissions	EN55022 "B", FCC Part 15 Subject J Class B
Safety Approvals	ANSI / EN 60601-1, UL/cUL/EN 60950-1 CE Mark (LVD)



## APS152EMG SERIES:

**Output Specifications:**

Model:	Vout	Max Output Current
APS152EMG-S120110 - <i>p x- ccc</i>	12V	10A
APS152EMG-S240060 - <i>p x- ccc</i>	24V	6A

- Replace "p" with the options below to designate the desired AC inlet option below:  
 Suffix "8" Package: 2-Prong IEC-320 C8 Inlet  
 Suffix "7L" Package: 3-Prong IEC-320 C6 Inlet  
 Suffix "7" Package: 3-Prong IEC-320 C14 Inlet
- Optional LED Indicator, replace x with the following:  
 Blank - no LED indicator  
 A = LED Indicator
- Replace "ccc" with output connector option desired as defined here: <http://advpower.com/dcconnector.pdf>

**OUTLINE DRAWING:**

